Data sheet
LIGA.AIR.DALI.240

- **Smallest DALI modul for 100VAC to 240VAC, for up to 50 DALI members**
- **Smallest power consumption 3 Watts max**
- **Simply operate with Casambi**

The DALI module LIGA.AIR.DALI.240 is directly controlled by the Casambi app.

The module is directly connected to 100-240 VAC line voltage.
The DALI-BUS output has a capability to drive an output current up to 100mA.

The module is capsuled in a black ABS housing with the dimensions of 38 x 38 x 26mm.

The extremely compact design of the housing allows an easy installation in flush-mounted boxes or in a cable duct.

Dimensional drawing:



Schematics:



Installation only by a professional electrician according to the local regulations!

LICHTTEAM AG
Stationsstrasse 89
CH 6023 Rothenburg
+41 41 280 57 57
mail@ligaair.ch
www.ligaair.ch

Data sheet
LIGA.AIR.DALI.240

Technical specifications:

Dimension (T x B x H)	38 x 38 x 26mm
Weight	65g
Color	Enclosure schwarz
Mounting	In flush-mounted boxes or cable ducts etc.
Environmental conditions	Operation: Temperature -20 ... 50°C, humidity < 85%rH Stock: Temperature -25 ... 65°C, humidity < 95%rH
Protection type / Protection class	IP64, EN-60529 / Appliance Class II
Connections	Cable 2 x 0.75mm² (AWG18), L = 150mm: Brown (BN): L, phase conductor Blue (BL): N, neutral conductor
Power supply / Frequency	100-240V~, 50-60Hz
Power consumption	3 Watts max
DALI output	Cable 2 x 0.75mm² (AWG18), L = 150mm: 2 x Black (BK), DALI BUS voltage 17 Volt Output current 100mA max (for approx. 50 Dali members)
Standards	Low Voltage Directive (LVD) 2014/35/EU, EN 60669-2-1 Electromagnetic compatibility (EMC) 2014/30/EU
CASAMBI Modul Standards	Bluetooth Wireless Control
Dimming and switching	Settable by the Casambi application (App Store, Google Play)
Applications	Dimming and switching of DALI devices, 1 channel or broadcast
Scope of delivery	1 DALI module

Compatible devices:

Download on the App Store

ANDROID APP ON Google play

Range:

Casambi uses mesh network technology so each CBU-ASD acts also as a repeater.

Longer ranges can be achieved by using multiple Casambi units.

Range is highly dependent on the surrounding and obstacles, such as walls and building materials.

LICHTTEAM AG
Stationsstrasse 89
CH 6023 Rothenburg
+41 41 280 57 57
mail@ligaair.ch
www.ligaair.ch